

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 06237106 A

(43) Date of publication of application: 23 . 08 . 94

(51) Int. Cl.
H01P 11/00
H01B 1/02
H01P 7/08

(21) Application number: 05022681

(22) Date of filing: 10 . 02 . 93

(71) Applicant: MATSUSHITA ELECTRIC IND CO LTD

(72) Inventor:
INOUE TATSUYA
KAGATA HIROSHI
KAMEYAMA ICHIRO
KATO JUNICHI

(54) LAMINATION TYPE ELEMENT FOR MICROWAVE

a higher no load Q value is used for the dielectric layer 1.

(57) Abstract:

COPYRIGHT: (C)1994,JPO&Japio

PURPOSE: To obtain the small sized lamination type element manufactured by an easy baking condition and having an excellent microwave characteristic by employing a specific Ag/Pd alloy to part or all of a conductor.

CONSTITUTION: The lamination type dielectric resonator has a structure that each of strip line conductors 2-4 is inserted between dielectric layers 1 to incorporate a shield conductor and a coupling capacitor as a lamination microwave element. The inner conductors 2-4 of the lamination type dielectric resonator are arranged at a prescribed interval via the dielectric layer 1 and they are connected respectively to an external electrode 5. All or part of the conductors 2-4 is made of an Ag/Pd alloy including 80wt.% or over of Ag. That is, the Ag/Pd alloy with a higher conductive rate comparatively except Ag,Cu,Au is employed for the conductors 2-4 of the microwave lamination type element, then a temperature at which simultaneous baking is attained is increased up to nearly 1050°C, the environment control is not required, the selection of the dielectric layer 1 is extended and the dielectric body having a higher dielectric rate and

